



Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

REC'D 27 JUL 2004

WIPO

PCT

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-
gen stimmen mit der
ursprünglich eingereichten
Fassung der auf dem näch-
sten Blatt bezeichneten
europäischen Patentanmel-
dung überein.

The attached documents
are exact copies of the
European patent application
described on the following
page, as originally filed.

Les documents fixés à
cette attestation sont
conformes à la version
initialement déposée de
la demande de brevet
européen spécifiée à la
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03016060.0

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

BEST AVAILABLE COPY

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk



Anmeldung Nr:
Application no.: 03016060.0
Demande no:

Anmeldetag:
Date of filing: 15.07.03
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

SIEMENS AKTIENGESELLSCHAFT
Wittelsbacherplatz 2
80333 München
ALLEMAGNE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se référer à la description.)

In Anspruch genommene Priorität(en) / Priority(ies) claimed /Priorité(s)
revendiquée(s)
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

H05K7/00

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL
PT RO SE SI SK TR LI

Description

COMPONENT CARRIER

5 The present invention relates to the general field of carrier components and more particularly to an improved carrier for components, the components including displays and the like, as set out in claim 1 and to a method for making such carriers as set out in claim 9. Component carriers
10 generally comprise a frame surrounded by a sealing lip. The combination of the frame and lip form a frame in which a component may be housed. The components generally include displays and other such sensitive electronic devices. The devices generally define a front and rear direction depending
15 upon application of the component. For example, a display defines a front direction which projects forward to an intended viewer displayed information. The rear of a display is generally characterized by electronic components in need of protection against mechanical stresses as well as
20 environmental effects. The aforementioned stresses and effects adversely impact and therefore limit utility of the life of the component. The stresses and effects generally arise out of implementation and environment of use.

Continuing with the display example, a common application for
25 displays is in automobiles and other moving vehicles. Such vehicles exist in a rugged world subject to external impacts, being both mechanical force, as due to typical application of the vehicle, and environmental effects depending upon the vehicle operating environment. An additional source of
30 stress and effect arise during assembly, both of the component to carrier and carrier into a larger (e.g. vehicular) housing. The stress and effect typify the problems facing use of components in intended, sometimes

harsh, working environments. Accordingly, a solution or need exists for a component carrier that offers tolerance against stress and effect.

Current solutions to the above problem include applying
5 two separate seals to a metal frame. Such seals generally are made of foam and comprise loose-bending pieces. Use of such seals include several problems. Application of the seals requires supporting tools of high position precision along with a visual inspection capability. Such tools are
10 required given the variety of metal frames in application to which the seals are to be applied. In addition, given the foam composition, the seals tend to be not so deformable, thereby not providing a high degree of mechanical force absorption or protection. In addition, such seals include a
15 high cycle time which reduces functional expediency of both carrier and component. Accordingly, a need or solution exists for a component carrier with improved resistance to mechanical and environmental stresses as well as improved manufacturing.

20 A solution to the above problems is set out by the present invention. The present invention is directed to a component carrier which includes a combination of a frame and a single sealing lip. The frame may be made of metal and include walls defining an interior cavity. The sealing lip
25 may be made of thermoplastic elastomer formed in a double sided sealing lip.

An object and advantage of the present invention is therefore to provide the above component carrier combination in a cost efficient and effective manner. This and other
30 objects and advantages are achieved by the sealing lip being dovetailed with a first arm longer than a second arm. The first arm may face front, a direction defined by application of the component. The sealing lip may further be applied by

a spraying process or an injection molding process, the both of which are well known in the art, less expensive than other processes and not requiring sophisticated equipment.

Further, the present carrier component may include recesses or openings along a surface of the walls defined the interior cavity. The openings may be an open V shape facing into the cavity. The recesses provide for a gripping point for the elastomer to adhere to during the cooling process. Accordingly, the sealing lip can maintain its form.

These and further aspects and advantages of the invention will be discussed more in detail hereinafter with reference to the disclosure of preferred embodiments, and in particular with reference to the appended Figures that show:

Figure 1 depicts a first view of a first frame according to an embodiment of the present invention;

Figure 2 depicts a second view of the first frame;

Figure 3 depicts a sealing lip without a frame;

Figure 4 depicts a sealing lip and frame combination;

Figure 5 depicts a second view of a sealing lip and first frame combination;

Figure 6 depicts a third view of a sealing lip and first frame combination;

Figure 7 depicts a first view of a second frame;

Figure 8 depicts a second view of the second frame;

Figure 9 depicts a first view of a combination of the sealing lip and second frame; and

Figure 10 depicts a second view of the combination of the sealing lip and second frame.

Throughout the specification, like reference numerals refer to equivalent elements. Figure 1 depicts a first view of the first frame 10. The frame may be made of metal and/or other

such material. As shown, first frame 10 includes walls 14 defining an internal cavity 12 and an external region 16. The internal region includes an internal border 18 surrounding cavity 12. Border 18 includes openings 20. The openings may be of any number as required by design. In this embodiment, the openings 20 are shaped as open V's with the bottom most point of the V facing cavity 12. As depicted, the first frame 10 includes eight openings. Other shapes are also applicable as required by design. A border of walls 14 proximate to the external region 16 are bent or folded over in an approximate perpendicular angle. The border walls continue in a direction away from a plane comprising cavity 12 and will herein be referred to as secondary walls 22. Secondary walls 22 include a variety of shapes, continuous or discontinuous, with aperture 24 or without 26, and other design features as may be required by application. Utility of the secondary walls is to affix to other elements (not shown) so as to secure the frame (and whatever may be attached to the frame) to the other elements. The first frame may further include openings 28 along side walls 30, and in a direction away from cavity 12. The openings 28 facilitate handling of the frame.

Figure 2 depicts the frame of figure 1 with measurement values assigned to certain features. The measurement values are by way example only, approximate, and do not restrict the invention to only these values. Other values are available as would be imagined by one skilled in the art. The open V openings 20 are depicted as defining an angle of ninety degrees 32. A center line 34 of openings 20 is located approximately 12 mm from a nearest side wall 30. Openings 20b not proximate to a side wall have a distance 42 of 25 mm between their center lines 36 and other openings 20a closer to side walls 30. The openings 20 define a depth 38 of 1.5

mm into walls 14, as well as an opening length 40 of 0.5 mm. Cavity 12 has a center line 44 which is 10.25 mm from a perpendicular lateral internal wall surface 46.

Figure 3 depicts a sealing lip 50 without a frame. The sealing lip is associated with first frame 10. The sealing lip may comprise thermoplastic elastomer. As is known in the art, thermoplastics are materials that soften or melt when heated and harden when cooled. The term elastomer, a contraction of the words elastic and polymer, is defined as a substance that can be stretched at room temperature to at least twice its original length and, after having been stretched and the stress removed, returns with force to approximately its original length in a short time. Thermoplastic polymers consist of long polymer molecules that are not linked to each other, i.e., have no cross-links. They are often supplied as granules and heated to permit fabrication by methods such as molding or extrusion. Returning to figure 3, the sealing lip 50 comprises walls 52 defining an internal cavity 54 and an external region 56. The sealing lip is a single piece which may be made from injection molding and/or spraying, techniques well known in the art. The walls comprise a dove tail formation, extending outward from the internal cavity 54 towards external region 56 in their respective directions and on either side of walls 14. The dove tails form a V shape 58. Along the V shape 58 are spacers 60 which corresponds in size and number to openings 20. The spacers 60 facilitate gripping by the thermoplastic elastomer of sealing lip 50 to frame 10 during cooling of the elastomer. Cavity 54 corresponds to cavity 12 of the first frame 10. Likewise, walls 52 correspond to frame walls 14. When formed, sealing lip 50 is molded and/or sprayed about first frame 10. The V shape 58 includes two arms 58a and 58b. As depicted, a forward direction 62 is in

a direction towards the bottom of the figure. Arm 58a, facing forward, is longer than arm 58b facing rearwards 64.

A cross section of frame 10 and sealing lip 50 is depicted in figure 4. The shaded areas 66 indicate portions which receive the injected molded or sprayed thermoplastic elastomer. The thickness 68 of arm 58a may be 0,5 - 3,0 mm and the thickness 70 of arm 58b may be 0,5 - 3,0 mm.

A side view of the frame 10 sealing lip 50 combination is depicted in figure 5, wherein it may be seen that frame 10 encases sealing lip 50. A component may be mounted with the sealing lip and attached to another element via frame 10.

Figure 6 depicts an elongated view of the frame sealing lip combination of figure 5. Herein, the secondary walls 22 are more visible.

Figure 7 depicts a perspective view of a second frame 72. Second frame 72, as first frame 10, includes walls 74 defining an internal cavity 76 and an external region 78. Furthermore, secondary walls 80 are also defined by walls 74, bent at substantially 90 degrees to a plane include cavity 76. Length of walls 74 between an internal border defining cavity 76 and border indicating the above bending, is 4.15 mm. The length of the second frame 72 is 79 mm plus or minus 0.15 mm. The aforementioned measurement values are descriptive only, with other values considered within the scope of the invention, the other values known to one skilled in the art. Side openings 82 are also depicted facing away from cavity 76.

Figure 8 shows another perspective view of the second frame 72 of figure 7. Figure 9 depicts a perspective view of a combination of sealing lip 50 as may be applied to second frame 72. The features of sealing lip 50 remain the same as detailed above. Lastly, figure 10 depicts a cross section of the combination of sealing lip 50 and second frame 72.

Claims:

1. A component carrier comprising a frame and a doubled sided seal, the seal providing mechanical force tolerance and compensation for the component encased in the skeleton frame and seal, characterized in that:
 - the seal comprises thermoplastic elastomer, and
 - the frame comprises recesses for the elastomer to adhere to when the elastomer undergoes a cooling process.
2. The component carrier according to claim 1, wherein the seal comprises a single piece.
3. The component according to claims 1 and 2, wherein the seal is applied to the frame by one of spraying and injection molding.
4. The component carrier according to claims 1-3, wherein the frame comprises walls defining an interior opening and the recesses are located along the interior opening.
5. The component carrier according to claims 1-4, wherein the recesses are open V shaped.
6. The component carrier according to claims 1-5, wherein the seal is dovetailed comprising two extending arms, a first of the two arms being longer than a second.
7. The component carrier according to claim 6, wherein the first arm faces a front, the front defined by application of the component.

20035033242
8. The component carrier according to claims 1-7, wherein the component is a display.

5 9. A method of making a component carrier, characterized by:

- injection molding and/or spraying a seal around a frame, the frame comprising walls defining an interior cavity with recesses along cavity walls, and the seal being molded in the shape of a dovetail,
- 10 - cooling the injection molding such that the molding adheres to the recesses.

10. The method according to claim 9, wherein the injection
15 molding comprises thermoplastic elastomer.

ABSTRACT

COMPONENT CARRIER

5 The present invention relates to a component carrier which includes a frame and a sealing lip. The frame includes walls defining an internal opening. The frame may be made of metal and the sealing lip of thermoplastic elastomer. The sealing lip is a single piece which is applied to the frame
10 by injection molding or spraying. The frame may further include recesses or openings along the walls defining its cavity. The cooling thermoplastic elastomer may then grip or adhere to the walls so as to retain its shape. The current invention provides increased compensation tolerances for
15 components accommodated therein.

Figure 9




FIGURE 1




FIGURE 3

2003P05592 EP

FIGURE 4







FIGURE 2



2003P05592 EP


FIGURE 6





2003P05592 EP

Figure 8







FIGURE 9

FIGURE 10



List of Elements

- first frame 10
- walls 14
- 5 internal cavity 12
- external region 16
- internal border 18
- openings 20
- openings 20a
- 10 openings 20b
- secondary walls 22
- aperture 24
- without aperture 26
- (side wall) openings 28
- 15 side wall 30,
- open V angle 32
- center line 34
- center lines 36
- depth 38
- 20 opening length 40
- center line 44
- internal wall surface 46
- sealing lip 50
- walls 52
- 25 internal cavity 54
- external region 56
- V shape 58
- arm 58a, arm 58b
- spacers 60
- 30 forward direction 62
- rearwards 64.

2003P05592 EP

2

shaded areas 66

thickness 68 of arm 58a

thickness 70 of arm 58b

second frame 72

5 walls 74

internal cavity 76

external region 78

secondary walls 80

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ BLACK BORDERS

☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☐ FADED TEXT OR DRAWING

☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☐ LINES OR MARKS ON ORIGINAL DOCUMENT

☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.